

# CAPACITIES

Year	Model	Engine		Engine Oil with			Transmission			Drive Axle		Fuel Tank (gal.)	Cooling System (qts.)
		Displacement (Liters (cc))	Engine ID/VIN	Filter (qts.)	(pts.)			Case (pts.)	Front (pts.)	Rear (pts.)			
					4-Spd	5-Spd	Auto.						
1997 (cont)	F-350	5.8 (5752)	H	6.0	—	7.6	⑨	⑧	6.0	6.0 ④	⑦	⑭	
		7.3 (7292)	F	14.0	—	7.6	⑨	⑧	6.0	6.0 ④	⑦	23.0	
		7.5 (7538)	L	6.0	—	7.6	⑨	⑧	6.0	6.0 ④	⑦	19.8	
	F-Super Duty	5.8 (5758)	R	7.0	—	7.0	24.0	⑧	6.0 ④	6.0 ④	35.0	23.0	
		7.3 (7292)	F	14.0	—	7.6	⑨	⑧	6.0	6.0 ④	⑦	23.0	
1998	Expedition	4.6 (4588)	6	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9	
		4.6 (4588)	W	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9	
		5.4 (5409)	L	7.0	—	—	⑨	4.0	3.7	5.5	30.0	20.8	
	F-150	4.2 (4195)	2	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	15.7 ⑪	
		4.6 (4588)	6	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
		4.6 (4588)	W	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
	F-250	5.4 (5409)	L	7.0	—	7.6	⑨	4.2	6.0	6.0	30.0	19.8	
		4.6 (4588)	6	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
		4.6 (4588)	W	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
	F-350	5.4 (5409)	L	7.0	—	7.6	⑨	4.2	6.0	6.0	30.0	19.8	
		5.8 (5758)	R	7.0	—	7.0	24.0	⑤	6.0 ④	6.0 ④	35.0	23.0	
		6.8 (6802)	5	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.3 (7292)	F	14.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.5 (7538)	G	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
	F-Super Duty	5.4 (5409)	L	7.0	—	7.6	⑨	4.2	6.0	6.0	30.0	19.8	
		5.8 (5758)	R	7.0	—	7.0	24.0	⑤	6.0 ④	6.0 ④	35.0	23.0	
		6.8 (6802)	5	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.3 (7292)	F	14.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.5 (7538)	G	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
	Navigator	4.6 (4588)	6	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9	
		4.6 (4588)	W	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9	
5.4 (5409)		L	7.0	—	—	⑨	4.0	3.7	5.5	30.0	20.8		
1999-00	Expedition	4.6 (4588)	6	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9	
		4.6 (4588)	W	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9	
		5.4 (5409)	L	7.0	—	—	⑨	4.0	3.7	5.5	30.0	20.8	
	F-150	4.2 (4195)	2	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	15.7 ⑪	
		4.6 (4588)	6	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
		4.6 (4588)	W	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
		5.4 (5409)	L	7.0	—	7.6	⑨	4.2	6.0	6.0	30.0	19.8	
	F-250	4.6 (4588)	6	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
		4.6 (4588)	W	6.0	—	7.6	26.0	4.0	3.7	5.5	24.5 ⑩	17.9	
		5.4 (5409)	L	7.0	—	7.6	⑨	4.2	6.0	6.0	30.0	19.8	
	F-350	5.4 (5409)	L	7.0	—	7.6	⑨	4.2	6.0	6.0	30.0	19.8	
		5.8 (5758)	R	7.0	—	7.0	24.0	⑤	6.0 ④	6.0 ④	35.0	23.0	
		6.8 (6802)	5	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.3 (7292)	F	14.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.5 (7538)	G	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
	F-Super Duty	5.4 (5409)	L	7.0	—	7.6	⑨	4.2	6.0	6.0	30.0	19.8	
		5.8 (5758)	R	7.0	—	7.0	24.0	⑤	6.0 ④	6.0 ④	35.0	23.0	
		6.8 (6802)	5	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.3 (7292)	F	14.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
		7.5 (7538)	G	7.0	—	7.6	⑨	4.2	6.0 ④	6.0 ④	35.0	23.0	
	Navigator	4.6 (4588)	6	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9	
4.6 (4588)		W	6.0	—	—	⑨	4.0	3.7	5.5	26.0	17.9		
5.4 (5409)		L	7.0	—	—	⑨	4.0	3.7	5.5	30.0	20.8		

NOTE: All capacities are approximate. Add fluid gradually and check to be sure a proper fluid level is obtained.

① New Process: 9 pts. Dextron II

BW 1354: 6.5 pts. Dextron II

BW 1356: 4 pts. Mercon II

② With OD: 4.5 pts.

③ 4WD: 27 pts.

④ Heavy duty: 7.5 pts.

⑤ Mazda M50D: 7.6

S5-42 ZF: 7.0

⑥ C6 transmission with 2WD: 23.5

C6 transmission with 4WD: 27

AOD transmission: 24.6

E40D transmission with 2WD: 31

E40D transmission with 4WD: 32

⑦ 124 inch Wheelbase: 18 gal.

138, 158 or 176 inch Wheelbase with front tank: 22 gal.

138, 158 or 176 inch Wheelbase with rear tank: 16 gal.

⑧ Without PTO: 4.2 pts.

With PTO: 12.0 pts.

⑨ With 4R70W: 28 pts.

With E40D: 32.0 pts.

⑩ Also available with a 30 gallon tank with 8 ft. box

⑪ Includes recovery reservoir

⑫ 4.9L without AC: 13.0 qts.

4.9L with AC or supercooling: 14.0 qts.

4.9L with AC and supercooling: 15.6 qts.

⑬ 5.0L with manual trans. and standard cooling system: 15.7 qts.

5.0L with automatic trans. and standard cooling: 16.5 qts.

5.0L with manual/automatic trans. and AC: 16.4 qts.

5.0L with manual/automatic trans. with supercooling/AC: 18.3 qts.

⑭ Manual trans. with standard cooling: 15.7 qts.

Automatic trans. with standard cooling: 16.4 qts.

Manual/automatic trans. with AC: 16.4 qts.

Manual/automatic trans. with supercooling and AC: 18.0 qts.

⑮ New Process: 9 pts. Dextron II

BW 1345: 6.5 pts. Dextron II

BW 1356: 4 pts. Mercon